

SLK-R602 Series Industrial 4G/3G Router

Specification

DATA: 2015-6-6



SLK-R602 Series Industrial Cellular Router



SLK-R602 is an industrial-grade high-speed wireless router based on GPRS/CDMA/WCDMA/EVDO/LTE cellular mobile network to provide users with high-speed wireless Internet and wireless data transmission functions.

This product adopts industrial-grade dedicated communication 32-bit RISC processors, industrial-strength wireless mold piece, the LINUX embedded real-time operating system, support a SIM card interface, four LAN, a WAN port, and WIFI interface, at the same time provide LAN port equipment or WIFI Internet or data transmission function.

It also adopts wide temperature, wide voltage input and EMC test with electromagnetic compatibility.

Has been widely used in the Internet of things industry chain of M2M industry, such as self-service terminals, smart grid, smart transportation, smart home, financial, mobile POS terminals, supply chain automation, industrial automation, intelligent buildings, fire control, public security, environmental protection, meteorology, digital medical treatment, telemetry, military, space exploration, agriculture, forestry, water, coal, petrochemical and other fields

Features:

- ✓ LTE Band Support
 - EU Model: 2100/1800/2600/900/800 MHz (B1/B3/B7/B8/B20)
 - US Model: 1900/AWS/850/700/700/1900 MHz
 - (B2/B4/B5/B13/B17/B25)
- ✓ Built-in high speed 2-port Ethernet switch,2x LAN port
- ✓ 1X WAN port
- ✓ Power input supported DC6-28VDC
- ✓ The power and the antenna with lightning protection.
- ✓ Support VPN client(PPTP, L2TP, OPENVPN, IPSEC and GRE)(only for VPN version)
- ✓ Support hardware and software WDT

Web: www.seriallink.net e-Mail: info@seriallink.net Mobile Phone: +86-18682315199

Address: A602, Bldg A ,ShenMa Industrial district , Nanwan Street, Longgang District Shenzhen Guanadona China (Mainland)



SLK-R602 Series Industrial Cellular Router

Details:

Cellular Interface:

Cellular Interface				
Band Supported	4G/3G/2G Version	 Supported TDD-LTE B38/B39/B40/B41 Supported FDD-LTE B1/B3/B5/B8 Supported FDD-LTE B1/ B3/ B5/ B7/ B8/B12/ B20 Supported FDD-LTE B1/ B2/ B3/ B4/ B5/ B7/ B8/ B28 Supported TD-SCDMA B34/B39 Supported WCDMA/HSDPA/HSPA+ B1/B8 Supported CDMA 1X/EVDO BC0 Supported GSM/GPRS/EDGE 900/1800 MHz 		
	EVDO 3G Version	Supported EVDO, CDMA2000 1X		
	HSDPA 3G Version	Supported HSUPA/HSDPA/UMTS/EDGE/GPRS/GSM		
Theory of Bandwidth	 LTE CAT4- DL: 50Mbps, UL: 150Mbps TD-HSDPA/HSUPA-DL: 2.2 Mbps, UL: 2.8 Mbps HSPA+-DL: 5.76 Mbps, UL: 42 Mbps WCDMA – DL/UL: 384Kbps CDMA2000/EVDO DL: 1.8 Mbps, UL: 3.1 Mbps 			

WIFI Performance:

WIFI supported	
Standards	Supported IEEE 802.11 b/g/n
Frequency	2.4GHz (ISM band supported)
WIFI Rate	150Mbps
Security	64/128-bit WEP (Wired Equivalent Privacy)
	WPA & WPA-PSK &WPA2 -PSK(Wi-Fi Protected Access)

Router characteristics		
Firewall	Network Address Translation (NAT)	
	State full Packet Inspection (SPI)	
Media	CSMA/CA with ACK	
Access Control	ACSIMATOR WILLIAGR	
VPN protocol	Supported IPSec,PPTP,L2TP	
DHCP	Build-in DHCP (Dynamic Host Configuration Protocol)	
Others protocol	Supported PPP,PPOE, DDNS,ICMP,VRRP etc	

Hardware:

Hardware	
CPU	32-bit high performance communication CPU,32bit/400MHZ
Flash/RAM	8M/64M
os	LINUX latest version

Web: www.seriallink.net e-Mail: info@seriallink.net Mobile Phone: +86-18682315199

Address: A602, Bldg A ,ShenMa Industrial district , Nanwan Street, Longgang District

Shenzhen Guanadona China (Mainland)



SLK-R602 Series Industrial Cellular Router

Interface:

Interface		
LAN 🏻	1 x 10/100M port	
WAN □	1x 10/100M WAN/LAN port	
Reset	1x Reset	
Antennas	1x 3G/4G Antenna(50Ω SMA interface)	
	1x WiFi or GPS antenna (option)	
LED	Power-SYS-LAN-WiFi-3G/4G LED	
SIM slot	Supported 1.8/3.3V SIM card	1 / /
	we support SIM card converter meet all size sim card	

Power interface:

Power			
Default power	DC 12V/1A power adapter (US,EU etc stander option)		
Input VDC	6~28V		
	Min: 260mA@12VDC		
Power Dissipation	MAX: 500mA@12VDC		
	Average:320mA@12VDC	\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \	

Physical property:

Physical property:	
Operating	Storage Temperature: (-30°C to 70°C)
Temperature	Operating Temperature: (-40°C to 75°C)
Relative Humidity	95%
Size	L*S*H: 98m x60mm x 24mm
Weight	Net weight:400g
	Packing weight: 1kg

Others:

other	
Warranty	5 years
Package contains	Seriallink Router,1.5m long RJ45 Cable,12V/1A Power Adapter,Antennas User manual(Option choose PDF),Warranty card, CERTIFICATION

Order information:

Model	LAN	LAN/WAN	SIM slot	WIFI/GPS	4G
SLK-R602LTE	1	1	1	1	1
SLK-R602HSDPA	1	1	1	1	1
SLK-R602EVDO	1	1	1	1	1

Web: www.seriallink.net e-Mail: info@seriallink.net Mobile Phone: +86-18682315199

Address: A602, Bldg A ,ShenMa Industrial district , Nanwan Street, Longgang District Shenzhen Guandong China (Mainland)